

cPCI-7230

16-CH Isolated DI & 16-CH Isolated DO Module

Features

- 3U Eurocard form factor, CompactPCI compliant (PICMG 2.0 R2.1)
- 16-CH isolated digital inputs and 16-CH isolated digital outputs
- Non-polarity digital input range
- 5000 V_{RMS} optical isolation
- Sink current up to 500mA on each isolated output
- Isolated input voltage up to 24 V
- Two external interrupt sources

Operating Systems

- Windows 2000/NT/XP/9x
- DOS
- Red Hat Linux
- Windows CE (call for availability)

Recommended Software

- VB/Vc++/BCB/Delphi
- DAQBench

Driver Support

- PCIS-DASK for Windows 2000/NT/XP/9x
- PCIS-DASK/X for Red Hat Linux
- PCIS-OCX ActiveX controls
- PCIS-LVIEW/PnP **NEW!**

1
Software
Solutions2
PXI/
CompactPCI
Platforms3
PXI-Based
Instruments4
PXI/
CompactPCI
Modules5
PCI DAQ
Cards6
PCI DIO
Cards7
PCI/104-Plus
Products8
ISA DAS/
DIO Cards9
Wiring
Termination
Boards10
Motion
Control
Cards11
Machine
Vision
Products12
Remote I/O
Modules

Introduction

ADLINK cPCI-7230 is a 16-CH isolated digital input and 16-CH isolated digital output module for PXI/CompactPCI form factor. The device provides a robust 5,000 V isolation protection which is suitable for most industrial applications. The wide input range makes the cPCI-7230 easy to sense the status of external devices. A potential difference of 3 to 24 V between two input terminals is logic high. Logic low is between 0 to 1 V. The device features a wide output range from 5 to 35 V, suitable for relay driving and industrial automation applications. It also provides two interrupt sources on digital input channels, which are easily user configurable.

Specifications

Isolated Digital Input

- Number of channels: 16 (IDI0-7 have individual connections and IDI8-15 share a common connection.)
- Maximum input range: 24 V, non-polarity
- Digital logic levels
 - 0-24V, non-polarity
 - ◆ Input high voltage: 3-24 V
 - ◆ Input low voltage: 0-1 V
- Input Resistance: 1.2 k Ω @ 0.5 W
- Isolation voltage: 5000 V_{RMS}
- Interrupt sources: digital input channel 0 and 1
- Data transfers: programmed I/O

Isolated Digital Output

- Number of channels: 16
- Output type: open collector Darlington transistor
- Sink current
 - 500 mA for one channel @ 100% duty
 - 500 mA for all channels @ 20% duty
- Power dissipation
 - Max. 2.25 W per chip (8 DO channels)
- Supply voltage: 5-35 V_{DC}
- Isolation voltage: 5000 V_{RMS}
- Data transfers: programmed I/O

General Specifications

- I/O connector: 50-pin SCSI-II female
- Operating temperature: 0 to 60 °C
- Storage temperature: -20 to 80 °C
- Relative humidity: 5 to 95%, noncondensing
- Power requirements

Device	+5 V
cPCI-7230	150 mA typical

- Dimensions (not including connectors)
160 mm x 100 mm

Termination Boards

DIN-50S

- Termination Board with a 50-pin SCSI-II Connector and DIN-Rail Mounting (Including One 1-meter ACL-10250 Cable)

Pin Assignment

VDD	1	26	VDD
EOGND	2	27	EOGND
EOGND	3	28	EOGND
EOGND	4	29	EOGND
IDO_7	5	30	IDO_14
IDO_6	6	31	IDO_15
IDO_5	7	32	IDO_12
IDO_4	8	33	IDO_13
IDO_3	9	34	IDO_10
IDO_2	10	35	IDO_11
IDO_1	11	36	IDO_8
IDO_0	12	37	IDO_9
IDI_3H	13	38	IDI_7L
IDI_3L	14	39	IDI_7H
IDI_2H	15	40	IDI_6L
IDI_2L	16	41	IDI_6H
IDI_1H	17	42	IDI_5L
IDI_1L	18	43	IDI_5H
IDI_0H	19	44	IDI_4L
IDI_0L	20	45	IDI_4H
IDI_11	21	46	IDI_15
IDI_10	22	47	IDI_14
IDI_9	23	48	IDI_13
IDI_8	24	49	IDI_12
EICOM	25	50	EICOM

Ordering Information

- **cPCI-7230**
16-CH Isolated DI & 16-CH Isolated DO Module

**www.systemtech.se**

Tel: 013-35 70 30
sales@systemtech.se
Linnégatan 14 • 582 25 LINKÖPING