

cPCIS-1100A[R]

3U CompactPCI Sub-system with 3U Enclosure, 32-bit 8-slot Backplane and ATX Power Supply



cPCIS-1100A

Configuration

Power Supply	APS-930XA: 300W ATX AC input power supply with cooling fan 48VDC or 24VDC model available for big quantity OEM project
System Backplane	cBP-3208 for cPCIS-1100A cBP-3208R for cPCIS-1100AR
Chassis Partition	7 slots for peripheral cards 3 slots for system module 1 slot for power switch 9 slots occupied by ATX power supply 1 slot for spared space

Note: External cooling system is required.

Ordering Information

Model number	Description/Configuration
cPCIS-1100A	3U cPCI Sub-system 3U Enclosure with 32-bit 8-slot backplane and 300W ATX AC-input power supply
cPCIS-1100AR	3U cPCI Sub-system 3U Enclosure with 32-bit 8-slot backplane and 300W ATX AC-input power supply, with rear I/O capability

Note: EMC blank panels are optional. All models above do not include any system or peripheral board.

cPCIS-1200[R]

3U CompactPCI Sub-system with 3U Enclosure, Dual Segments with ATX Power Supply



cPCIS-1200

Configuration

Power Supply for both segments	APS-930XA: 300W ATX AC input power supply with cooling fan 48VDC or 24VDC model available for big quantity OEM project
System Backplane for each segment	cBP-3204 for cPCIS-1200 cBP-3204R for cPCIS-1200R
Chassis Partition	3 slots for peripheral cards of each segment 3 slots for system module of each segment 9 slots occupied by ATX power supply (1 slot for power switch)

Note: External cooling system is required.

Ordering Information

Model number	Description/Configuration
cPCIS-1200	3U cPCI Sub-system 3U Enclosure with Dual 32-bit 4-slot backplane and 300W ATX AC-input power supply
cPCIS-1200R	3U cPCI Sub-system 3U Enclosure with Dual 32-bit 4-slot backplane and 300W ATX AC-input power supply, with rear I/O capability

Note: EMC blank panels are optional. All models above do not include any system or peripheral board.

cPCIS-1151[R]

3U CompactPCI Sub-system with 3U Enclosure, 32-bit 8-slot Backplane, LCD and CompactPCI Power Module



cPCIS-1151

Configuration

Power Supply	Power backplane: cBP-3061 Supports one in-rack 3U cPCI 8HP power module PICMG 2.11 47-pin power interface Available power module: cPS-H325/AC (250W) 48VDC or 24VDC model available for big quantity OEM project
System Backplane	cBP-3208 for cPCIS-1151 cBP-3208R for cPCIS-1151R
LCD	6.4" high brightness LCD with 640x480 resolution
Chassis Partition	10 slots for 6.4" LCD 6 slots for peripheral cards 3 slots for system module 2 slots for single 3U cPCI power module

Note: External cooling system is required.

Ordering Information

Model number	Description/Configuration
cPCIS-1151	3U cPCI Sub-system 3U Enclosure with chassis alarm, 6.4" LCD, 32-bit 8-slot backplane and one cPS-H325/AC
cPCIS-1151R	3U cPCI Sub-system 3U Enclosure with chassis alarm, 6.4" LCD, 32-bit 8-slot backplane and one cPS-H325/AC, with rear I/O capability

Note: EMC blank panels are optional. All models above do not include any system or peripheral board.