


TRION-2402-dSTG Differential universal input module

- **Sampling:** 24 bit; 204.8 kS/s per channel
- **Input types:** Voltage up to ±10 V
Strain gauge, bridge sensor, piezoresistive bridge
IEPE
RTD; Pt100 to Pt2000
Resistance, potentiometer



NEW
DEWE2

Dedicated Instruments

Instruments

Front-ends

Signal Conditioning

Components

Software

TRION-dSTG specifications					
Input channels	8 using RJ-45 sockets (TRION-2402-dSTG-8-RJ) 8 using DSUB 9 sockets (TRION-2402-dSTG-8-D, double-wide slotpanel) 6 using LEMO 1B sockets (TRION-2402-dSTG-6-L1B) 8 using LEMO 0B sockets (TRION-2402-dSTG-8-L0B)				
Sampling rate	204.8 kS/s per channel				
Resolution	24 bit				
Input ranges					
Voltage	±10, 30, 100, 300 mV, 1 V, 3 V, 10 V				
Bridge	1, 3, 10, 30, 100, 300, 1000 mV/V or mV/mA				
IEPE	±100, 300 mV, 1V, 3V, 10V				
Resistance	10, 30, 100, 300 Ω, 1, 3, 10, 30 kΩ				
Current	Depending on external Shunt				
Voltage input accuracy	±0.02 % of reading ± 0.02 % of range ±20 μV				
Gain drift	typical 10 ppm/°C max. 20 ppm/°C				
Offset drift	typical 0.3 μV/°C + 10 ppm of range, max 2 μV/°C + 20 ppm of range/°C				
linearity	typical 0.01 %				
Input impedance	100 MΩ				
Input bias current	< 1 nA				
Input configuration	Single ended or differential (programmable)				
Input coupling	DC, AC (0.16 Hz, 0.5 Hz, 3.4 Hz, 10 Hz); max. DC voltage when AC coupled: 50 V				
Excitation voltage	0 to 13.5 V _{DC} (programmable, 1 mV steps), 100 mA max. current, max 8 W per module				
Accuracy	±0.03 % ±1 mV				
Drift	±10 ppm/K ±50 μV/K				
Current limit	100 mA				
Protection	Continuous short to ground				
Excitation current	0.2 to 20 mA _{DC} (programmable, 1 μA steps)				
Accuracy	0.05% ±2 μA				
Drift	15 ppm/°C				
Compliance voltage	10 V				
Output impedance	>10 MΩ				
IEPE Excitation	4 mA ±10 %				
Compliance voltage	22 V				
Supported sensors	4- or 6-wire full bridge 3- or 5-wire ½ bridge with internal completion (software programmable) 3- or 4-wire ¼ bridge with internal resistor for 120 and 350 Ω (software programmable) 4-wire full bridge with constant current excitation (piezoresistive bridge sensors) Potentiometric; Resistance Resistance Temperature Detection: Pt100, Pt200, Pt500, Pt1000, Pt2000 (software linearization functionality depending on measurement software) IEPE (fixed 4 mA excitation)				
Bridge resistance	80 Ω to 10 kΩ @ ≤ 5 V _{DC} excitation				
Shunt calibration	Two internal shunt resistors 50 kΩ and 100 kΩ				
Shunt and completion resistor accuracy	0.05 % ±15 ppm/K				
Automatic bridge balance	±250 % of Range				
Typical SNR	Range	10 mV	100 mV	1 V	10 V
	100 S/s ≤ fs ≤ 1 kS/s	82 dB	101 dB	111 dB	112 dB
	10 kS/s < fs ≤ 102.4 kS/s	72 dB	92 dB	104 dB	107 dB
	102.4 kS/s < f ≤ 200 kS/s	69 dB	80 dB	81 dB	81 dB
Spurious free dynamic range		10 mV	100 mV	1 V	10 V
	100 S/s ≤ fs ≤ 1 kS/s	108 dB	128 dB	141 dB	141 dB
	10 kS/s < fs ≤ 102.4 kS/s	103 dB	123 dB	134 dB	136 dB
	102.4 kS/s < f ≤ 200 kS/s	99 dB	120 dB ⁽¹⁾ / 106 dB	133 dB ⁽¹⁾ / 106 dB	135 dB ⁽¹⁾ / 106 dB
Typical CMRR	90 dB @ 1 KHz 80 dB @ 10 KHz				
Analog anti aliasing filter	2 nd order Bessel, automatically set by sample rate				
Sample rate ≤ 1k S/s	2.5 kHz (-3 dB), 1.5 kHz (-1 dB)				
Sample rate ≤ 10 kS/s	25 kHz (-3 dB), 15 kHz (-1 dB)				
Sample rate > 10kS/s	250 kHz (-3 dB), 150 kHz (-1 dB)				
Bandwidth (-3 dB digital filter)					
1 kS/s ≤ fs ≤ 51.2 kS/s	0.494 fs				
51.2 kS/s < fs ≤ 102.4 kS/s	0.49 fs				
102.4 kS/s < fs ≤ 204.8 kS/s	0.38 fs				
Crosstalk fin 1 kHz [10 kHz]	120 dB [105 dB]				

→ continued on next page ...

Channel to channel phase mismatch	<60 nsec between channels using the same range
Common mode voltage	$\pm 10 V_{DC}$
Over voltage protection	$\pm 50 V_{DC}$
Supported TEDS chips	DS2406, DS2430A, DS2431, DS2432, DS2433
Typical power consumption ²⁾	Typ 10 W + excitation power
Voltage mode; no excitation	7 W
IEPE mode	7 W
350 Ω full bridge (5 V / 10 V)	7 W / 9.5 W
120 Ω quarter bridge 5 V excitation	8 W
Bridge mode without connected sensor	11.5 W ³⁾
Weight	Appr. 200 g (RJ45 version), appr. 250 g (LEMO version)

Cables for TRION-2402-dSTG modules

TRION cables				
	Connector	Termination	Length	TRION modules
TRION-CBL-RJ-OE-05-00	RJ45	open end	5 m	TRION-x-dSTG-x-RJ
TRION-CBL-RJ-D9-01-00	RJ45	DSUB-9 socket (DAQP-STG/MDAQ-STG compatible)	1 m	TRION-x-dSTG-x-RJ
TRION-CBL-RJ-BNC-01-00	RJ45	BNC	1 m	TRION-x-dSTG-x-RJ
TRION-CBL-L0B9-OE-05-00	LEMO 0B.309	open end	5 m	TRION-x-dSTG-x-L0B
TRION-CBL-L0B9-OE-01-00	LEMO 0B.309	open end	1 m	TRION-x-dSTG-x-L0B
TRION-CBL-L0B9-D9-0.5-00	LEMO 0B.309	DSUB-9 socket (DAQP-STG/MDAQ-STG compatible)	0.5 m	TRION-x-dSTG-x-L0B
TRION-CBL-L1B8-OE-05-00	LEMO 1B.308	open end	5 m	TRION-x-dSTG-x-L1B
TRION-CBL-L1B8-D9-0.5-00	LEMO 1B.308	DSUB-9 socket (DAQP-STG/MDAQ-STG compatible)	0.5 m	TRION-x-dSTG-x-L1B



TRION-CBL-RJD9-01-00



TRION-CBL-RJBN-01-00

Mating connector

Connector				
	Connector	Termination	Length	TRION modules
LEMO-FGG.1B.308.CLAD52Z	LEMO 1B.308	mating connector, for cable diameter 4.2 to 5.2 mm	-	TRION-x-dSTG-x-LEMO
LEMO-FGG.1B.308.CLAD62Z	LEMO 1B.308	mating connector, for cable diameter 5.2 to 6.2 mm	-	TRION-x-dSTG-x-LEMO
LEMO-FGG.1B.308.CLAD72Z	LEMO 1B.308	mating connector, for cable diameter 6.2 to 7.2 mm	-	TRION-x-dSTG-x-LEMO